

### SPECIFICATION

Product definition		: tufted loop pile
Gauge		: 1/10"
Pile fibre		: 100% polyprop
Pile weight		: 400 gr/m <sup>2</sup>
Pile height	ISO 1766	: 2.9 mm
Tile backing		: Bitumen
Total thickness	ISO 1765	: 5.9 mm
Total weight		: 3700 gr/m <sup>2</sup>
Tile size		: 50 x 50 cm

### PERFORMANCE

Use classification		: Class 31
Castor chair test	EN 985	: B, occasional use
Abrasion	EN 1963	: pass
Vettermann test	ISO TR 10361/EN 1471	: pass
Dimensional stability	EN 986	: pass
Thermal isolation	ISO 8302	: 0.10 m <sup>2</sup> K/W
Luxury class	LC2	: LC1
DOP-nr		: 1016-3612
Prodis-nr		: In application

### ELECTROSTATIC PROPERTIES

Static loading		: Anti-static
----------------	--	---------------

### FLAMMABILITY

Reaction to fire	EN ISO 9239-1	: C <sub>fl</sub> -s1
Reaction to fire	BS 4790	: Low radius of effects of ignition

### COLOUR FASTNESS

Light	ISO 105 B02	: 4.4
Rubbing	ISO 105 X12	: 5.0

### GENERAL

Maintenance: Regular vacuum cleaning is essential. Spills and surface stains can be removed by sponging with a damp cloth, or for more resistant stains, with a mild detergent solution.

