

# Arquisafe Arenal PUR



	Gauge	EN 428/ISO 24346	2.0mm
	Wear Layer	EN 429/ISO 24340	0.70mm
	Roll Size	EN 426/ISO 24341	2m x 20m = 40m <sup>2</sup>
	Total Weight	EN 430/ISO 23997	2780g/m <sup>2</sup>
	General Performance	EN 13845 ASTM F1303	Conforms Conforms
	Use Area	EN 685/ISO 10874	  
	Resistance to Chemicals	EN 423	Good chemical resistance
	Reaction to Fire	EN 13501-1 ASTM E648	Class Bfl-S1 Class 1
	Abrasion Resistance	EN 13845 EN 649	50,000 cycles Group T
	Enhanced Slip Resistance	EN 13845 AS 4586 DIN 51130 RRL Pendulum Test Surface Roughness	ESf R10 R10 ≥36 (wet test - 4S Rubber/Slider 96) Rz ≥20µm
The wet slip resistance across all Polysafe products is sustainable throughout the guaranteed life of the product, with strict adherence to HSE Guidelines. For further clarification regarding slip resistance, consult Polyflor.			
	Electrical Behaviour (body voltage)	EN 1815	≤2kV Classified as 'antistatic'
	VOC Emissions	Indoor Air Comfort GOLD AgBB VOC test Floorscore	Eurofins certified product Very low emissions Certified
	Responsible Sourcing	BES 6001	Excellent
	<b>Agrément Assurance</b> - has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance, colour and slip resistance will be retained during this period.		
	<b>Environmentally Preferable Flooring</b> - achieves BRE Global A+ rating (ENP 415) in the Green Guide to Specification in use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Silver Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. It is 100% recyclable and contains 10% recycled material. Recyclable via the Recofloor scheme.		
	features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention. As with all Polysafe products, Polysafe Arena PUR should not have a polish applied.		
	<b>Hygiene</b> - All commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.		
	flooring ranges have good resistance to dilute acids and alkalis, are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. Chemical resistance charts available on request. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult		
	As with all products, should not have a polish applied. For best results, flooring must be reversed laid. The data presented is correct at the time of printing. For latest information, please visit our website Decoration and shade may vary slightly from the samples shown.		

