

TECHNICAL CHARACTERISTICS

			Lock 30	Lock 20
DESCRIPTION				
Total thickness	EN ISO 24346 (EN 428)	mm	4.0	3.4
Thickness of wearlayer	EN ISO 24340 (EN 429)	mm	0.30	0.20
Weight: Mass per unit area	EN ISO 23997 (EN 430)	g/sqm	7760	6782
Size	EN ISO 24342 (EN 427)	cm	planks: 94 x 15 124.5 x 17.8 tiles: 30.3 x 60.7	planks: 93.5 x 14.9 tiles: 30.7 x 60
Planks / Tiles per package	-	planks / tiles	planks: 94 x 15 = 14 124.5 x 17.8 = 8 tiles: 10	planks: 14 tiles: 10
Surface per package	-	sqm	planks: 94 x 15 : 14 = 1.97 124.5 x 17.8 = 1.77 tiles: 1.84	planks: 1.95 tiles: 1.84

CLASSIFICATION

Norm / Product specification	-	-	EN 649	
European classification	EN ISO 10874 (EN 685)	class	23/31	22
Fire rating - Classification	EN 13501-1	class	B _f -s1	
Static electrical propensity	EN 1815	kV	< 2	
Slip resistance wet: ramp test with oil	DIN 51130	class	R9	

PERFORMANCE

Wear Group	EN 649	group	T	
Dimensional stability after exposure to heat	EN ISO 23999 (EN 434)	%	≤ 0.15	≤ 0.10
Residual indentation	EN ISO 24343-1 (EN 433)	mm	≤ 0.10	≤ 0.10
Impact sound insulation	EN ISO 717-2	dB	4	5
Room impact noise	NF S 31074	dB	76	-
Thermal conductivity	EN ISO 10456 (EN 12524)	W/(m.k)	0.25	
Colour fastness	EN 20 105 - B02	degree	≥ 6	
Surface treatment	-	-	PUR+	PUR
Guarantee for residential use	-	year	12	11

ENVIRONMENT / INDOOR AIR QUALITY

TVOC after 28 days	ISO 16000-6	µg/m ³	< 100	
VOC rating (French norm)	-	-	A+	

CE MARKING



EN 14041



Areas of use: domestic use



HEALTH

- Formaldehyde-free
- Lead-free, no heavy metals
- Solvent-free
- No harmful plasticizer
- Low VOC emission
- No glue

ENVIRONMENT

- ISO 14001
- Soapy water cleaning

Laying video

