

BAILARINA

1. Technical Specifications

Issued by: Graboplast Floor Covering Manufacturers Ltd. (H-9023 Győr Fehérvári út 16/b.)

Purpose: Technical data of the resilient **heterogeneous Type I. PVC flooring** according to **EN ISO 10582 / EN 649** sheet vinyl.

2. Application Area

For use area of light domestic (21) objects. Floor covering for light traffic. For information on handling of the product (storing, installation, maintenance) see www.graboplast.com.

3. Technical Data of the Product

Parameter	Dimension	Specification	Tolerance	Test method
Width	cm	200	min.	EN ISO 24341
Thickness	mm	1.4	+0.13; -0.10	EN ISO 24346
Weight	g/m²	2000	+13%; -10%	EN ISO 23997
Wear layer density	kg/m³	1250	±50	EN ISO 23996
Dimensional stability (L/C)	%	±0.2	max.	EN ISO 23999
Curling	mm	8	max.	EN ISO 23999
Flexibility	-	no damage	-	EN ISO 24344
Light fastness	grade	6	min.	EN ISO 105-B02 3. method
Abrasion group	-	T	-	EN 660-2
Wear layer thickness	mm	0.5	+13%; -10%	EN ISO 24340
Castor chair	-	slight change	max.	ISO 4918 / EN 425
Residual indentation	mm	0.1	max.	EN ISO 24343

4. Informative Data of the Product

Parameter	Dimension	Specification	Tolerance	Test method
Chemical resistance	-	high resistance	-	EN ISO 26987
Hot weld strength	N/50 mm	240	min.	EN 684
Slip resistance	class	DS	-	EN 13893
Reaction to fire	class	C_fS₁	-	EN 13501-1
Standard roll length	m	20	-	EN ISO 24341

Valid from: 27.09.2018