

# Grabo Aura

Technical parameter	Standard	Unit	Result
<b>DESCRIPTION</b>			
Construction			Light-Commercial heterogeneous
Total thickness	EN ISO 24346	mm	2.0
Width of roll	EN ISO 24341	m	2 / 4
Length of roll	EN ISO 24341	lm	25
Total weight	EN 430	kg/m2	1.8
<b>CLASSIFICATION</b>			
European classification	ISO 10874	class	23/32/41
Residual indentation	EN ISO 24343-1	max. mm	0.2
Dimensional stability	EN ISO 23999	max.%	0.2
<b>PERFORMANCE</b>			
Abrasion group	MSZ EN 660-1	class	T
Fire resistance	EN 13501-1	class	Bfl-s1
	DIN 51130		R9
Slip resistance	EN 13893		DS
Electrical resistance	EN 1815	kV	< 2
Chemical resistance	EN ISO 26987		✓
Bacterial resistance	EN ISO846:1999		✓
Light fastness	EN 20105 B02	grade	min.6
Castor chair resistance	ISO 4918		✓
Enviromental attributes			Solvent and heavy metal free 100% recyclable
Content of PCP	EN 12673		No
Formaldehyde emission	ENV 717-1		E1 (No Emission)
Seaming method			heat or cold weld
<b>Warranty</b>		<b>year</b>	<b>7</b>
<b>CE MARKING</b>	<b>EN 14041</b>		✓

**GRABOPLAST Floor Covering Manufacturers Ltd.**  
H-9023 Győr, Fehérvári út 16/b tel.: (36) 96 506 100  
mail@graboplast.hu www.graboplast.hu