

# Polysafe™ Verona PUR

Polysafe Verona PUR is ideal for use in areas where contaminant spillages can occur, making slip resistance an important consideration. Typical areas include circulation areas and corridors, dining areas and cafes, classrooms, hospital wards, clinics, laundry and sluice rooms, nursing homes, washrooms, WCs, bar serveries, food preparation areas, canteens and institutional applications. For continually wet areas please refer to our Polysafe Hydro, Hydro Evolve or Quattro ranges.



|   |  |   |   |
|---|--|---|---|
|   | <b>Gauge</b>                               | EN 428/ISO 24346  | 2.0mm   |
|   | <b>Roll Size</b>                           | EN 426/ISO 24341  | 2m x 20m = 40m <sup>2</sup>   |
|   | <b>Total Weight</b>                        | EN 430/ISO 23997  | 2600g/m <sup>2</sup>  |
|   | <b>General Performance</b>                 | EN 13845<br>ASTM F1303  | Conforms<br>Conforms  |
|   | <b>Use Area</b>                            | EN 685/ISO 10874  |   |
|   | <b>Resistance to Chemicals</b>             | EN 423  | Good chemical resistance  |
|   | <b>Reaction to Fire</b>                    | EN 13501-1<br>ASTM E648<br>Aus NCC Spec C1.10-3   | Class Bfl-S1<br>Class 1<br>Complies   |
|   | <b>Abrasion Resistance</b>                 | EN 13845<br>EN 649  | 50,000 cycles<br>Group T  |
|   | <b>Enhanced Slip Resistance</b>            | EN 13845<br>AS 4586 Appendix A<br>AS 4586 Appendix D<br>DIN 51130<br>RRL Pendulum Test<br>Surface Roughness   | ESf<br>P3<br>R10<br>R10<br>≥36 (wet test - 4S Rubber/Slider 96)<br>Rz ≥20µm |
| <p>The wet slip resistance across all Polysafe products is sustainable throughout the guaranteed life of the product, with strict adherence to HSE Guidelines. For further clarification regarding slip resistance, consult Polyflor.</p>   |  |   |   |
|   | <b>Electrical Behaviour (body voltage)</b> | EN 1815   | ≤2kV Classified as 'antistatic'   |
|   | <b>VOC Emissions</b>                       | AgBB VOC test<br>GBCA/NZGBC Green Star IEQ-VOC<br>Floorscore<br>Finnish M1 Classification   | Pass<br>Compliant<br>Certified<br>Certified                                 |
|   | <b>Responsible Sourcing</b>                | BES 6001  | Excellent   |
| <p><b>Agrément Assurance</b> - Polysafe Verona PUR has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance, colour and slip resistance will be retained during this period.</p>   |  |   |   |
| <p><b>Environmentally Preferable Flooring</b> - Polysafe Verona PUR achieves BRE Global A+ rating (ENP 472) in the Green Guide to Specification in use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Silver Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. It is 100% recyclable and contains recycled material. Recyclable via the Recofloor scheme. Visit <a href="http://www.polyflor.com/sustainability">www.polyflor.com/sustainability</a></p> |  |   |   |
| <p><b>Polysafe PUR</b> - Polysafe Verona PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention. As with all Polysafe products, Polysafe Verona PUR should not have a polish applied.</p>  |  |   |   |
|   | <b>Hygiene</b>                             | <p>All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.</p>   |   |
|   | <b>Safety</b>                              | <p>Polysafe safety flooring ranges have good resistance to dilute acids and alkalis, are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. Chemical resistance charts available on request. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email <a href="mailto:tech@polyflor.com">tech@polyflor.com</a>.</p> <p>As with all Polysafe products, Polysafe Verona PUR should not have a polish applied. The data presented is correct at the time of printing. For latest information, please visit our website <a href="http://polyflor.com">polyflor.com</a>.<br/>                     Decoration and shade may vary slightly from the samples shown.</p> |   |



**Polyflor UK** Sales Direct: +44 (0)161 767 1122 • Export Sales Direct: +44 (0)161 767 1913  
 Sample Requests: +44 (0)161 767 2551 • email: [info@polyflor.com](mailto:info@polyflor.com) • [www.polyflor.com](http://www.polyflor.com)

**Polyflor Australia** Tel: 1800 777 425 • email: [sales@polyflor.com.au](mailto:sales@polyflor.com.au) • [www.polyflor.com.au](http://www.polyflor.com.au)  
**Polyflor New Zealand** Tel: 0800 765 935 • email: [sales@polyflor.co.nz](mailto:sales@polyflor.co.nz) • [www.polyflor.co.nz](http://www.polyflor.co.nz)

