

CAMARO™

The Camaro range features a variety of different wood and stone textures designed to replicate the original material. These are both decorative and practical offering durability, sound reduction and the ability to install and maintain easily. Common use areas for Camaro include mainly residential or light commercial.



	Gauge	EN 428/EN ISO 24346	2.0mm
	Wear Layer	EN 429/EN ISO 24340	0.3mm
	Plank Size	EN 427/EN ISO 24342	192 @ 76.2 x 228.6mm = 3.34m ² 36 @ 101.6 x 914.4mm = 3.34m ² 24 @ 152.4 x 914.4mm = 3.34m ² 18 @ 152.4 x 1219.2mm = 3.34m ² 15 @ 184.2 x 1219.2mm = 3.37m ² 12 x 3 @ 76.2 / 101.6 / 152.4 x 914.4mm = 3.62m ² 14 @ 203.2 x 1219.2mm = 3.46m ²
	Total Weight	EN 430/EN ISO 23997	3600g/m ²
	General Performance	EN 649 EN ISO 10582	Conforms Conforms
	Use Area	EN 685/EN ISO 10874	
	Reaction to Fire	EN 13501-1	Class Bfl-S1
	Abrasion Resistance	EN 649 EN ISO 10582	Group T Type I
	Slip Resistance	EN 13893 DIN 51130 AS/NZS 4586	Class DS (dry condition) R10 R10
		For safety flooring with sustainable wet slip resistance, refer to Expona Control or the Polysafe ranges.	
	Indentation Residual	EN 433/EN ISO 24343-1	≤0.05mm
	Dimensional Stability	EN 434/EN ISO 23999	≤0.1% max
	Thermal Conductivity	ISO 8302	Suitable for underfloor heating. Max 27°C.
	Light Fastness	ISO 105-B02	(Method 3) ≥6
	Castor Chair (continuous use)	EN 425/ISO 4918	Suitable
	Electrical Behaviour (body voltage)	EN 1815	≤2kV Classified as 'antistatic'
	VOC Emissions	Indoor Air Comfort GOLD AgBB VOC test FloorScore	Eurofins certified product Very low emissions Certified product
	Responsible Sourcing	BES 6001 SA 8000	Very Good Approved factory
Environmentally Preferable Flooring - Polyflor Camaro PUR achieves BRE Global A+ rating (ENP 429). Generic EN 15804 Environmental Product Declaration (EPD) available on request. It is 100% recyclable and contains average 40% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability .			
PUR - Polyflor Camaro PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost, polish free maintenance regime for the lifetime of the flooring.			
	For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com . The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com . Decoration and shade may vary slightly from the samples shown.		

100% RECYCLABLE
40% RECYCLED MATERIAL

A+BRE
ENP 429
ENVIRONMENTAL
RATING

EPD
Environmental Product Declaration
Verified by EPD

Recofloor™
Vinyl Take-Back Scheme

POLYFLOR
PUR
POLISH FREE

BES 6001
Responsible Sourcing
www.greenbook3.com

GREEN ALLIANCE
POLYFLOR
GREEN ALLIANCE

floor score
GREEN ALLIANCE

nbs
BIM

nbsPlus

SGS

SGS

