

POLYFLOR CLASSIC MYSTIQUE PUR



2.0mm



2m x 20m = 40m²



300 x 300mm = 4.5m²
608 x 608mm = 5.17m²



3250g/m²



GENERAL PERFORMANCE
EN 649 / EN ISO 10581
ASTM F1913
ASTM F1700



REACTION TO FIRE
EN 13501-1 Class Bfl-S1
ASTM E662 <450
ASTM E648 Class 1



SLIP RESISTANCE
EN 13893 Class DS
AS/NZS 4586 R9



ABRASION RESISTANCE
EN ISO 10581 Type I



ELECTRICAL BEHAVIOUR
(body voltage)
EN 1815 <2kV
Classified as 'antistatic'



CASTOR CHAIR
(continuous use)
Suitable



AGRÉMENT ASSURANCE
Independently assessed by the BBA and awarded a 10 year product performance assurance in recommended use areas.



INDENTATION RESIDUAL
ASTM F970 (Modified)
Static load 750psi



RESPONSIBLE SOURCING
BES 6001 Very good



VOC EMISSIONS
Indoor Air Comfort GOLD Eurofins certified product
AgBB VOC test: Pass
Floorscore certified (SCS Certificate Reg No: SCS-FS-02034)
Finnish M1 Classification: Pass
Swedish B.P.D (FLEC test): Best Class
GBCA/NZGBC Green Star IEQ-VOC: Compliant



HYGIENE
All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



ENVIRONMENTALLY PREFERABLE FLOORING
Polyflor Classic Mystique PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 472) in major use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Gold Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. Classic Mystique PUR is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/environment



Polyflor Classic Mystique PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low cost, polish-free maintenance regime for the lifetime of the flooring.



APPLICATIONS
Polyflor Classic Mystique PUR is recommended for heavy traffic areas that require a homogeneous floorcovering that offers durability, reliability, ease of maintenance and aesthetic appeal. Ideally suited for the most demanding of areas within the Healthcare and Education sector, as well as Retail, Leisure and the Commercial environment.



Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
WEBSITE: WWW.POLYFLOR.COM

James Halstead
FLOORING



2011



Recofloor™
Vinyl Take-Back Scheme



POLYFLOR
CLASSIC MYSTIQUE PUR
HOMOGENEOUS



PERFORMANCE AND PROPERTIES



In collaboration with the European Resilient Flooring Manufacturers' Institute (ERFMI), Polyflor Ltd supports sustainable construction via Environmental Product Declarations (EPDs).

