

## POLYFLOR COLONIA WOOD PUR

- Colonia - collection of residential vinyl floor products
- Wood effect floorcovering designs
- Coordinating inlay strips to blend, shape or accentuate design ideas

### SPECIFICATION



2.0mm



0.2mm



36 @ 101 x 914mm = 3.34m<sup>2</sup>  
 24 @ 152 x 914mm = 3.34m<sup>2</sup>  
 18 @ 152 x 1219mm = 3.34m<sup>2</sup>  
 15 @ 184 x 1219mm = 3.37m<sup>2</sup>



3680g/m<sup>2</sup>



#### GENERAL PERFORMANCE

EN 649  
 EN ISO 10582



#### REACTION TO FIRE

EN ISO 13501-1 Class Bfl-S1



#### ABRASION RESISTANCE

EN 649 Group T  
 EN ISO 10582 Type 1



#### SLIP RESISTANCE

EN 13893 Class DS (dry condition)\*  
 DIN 51130 R10



For safety flooring with sustainable wet slip resistance, refer to Expona Control PUR or the Polysafe ranges



#### INDENTATION - RESIDUAL

EN 433 <0.05mm  
 EN ISO 24343-1 ≤0.05mm



#### DIMENSIONAL STABILITY

EN 434 ≤0.1% max.  
 EN ISO 23999 ≤0.1% max.



#### CASTOR CHAIR (continuous use)

EN 425 / ISO 4918 Suitable



#### THERMAL CONDUCTIVITY

Suitable for underfloor heating  
 Heating Max 27°C



#### LIGHT FASTNESS

ISO 105-B02 (Method 3) ≥6



#### BES 6001

Responsible Sourcing  
[www.greenbooklive.com](http://www.greenbooklive.com)

#### RESPONSIBLE SOURCING

BES 6001 Very good  
 SA 8000 Approved factory



#### VOC EMISSIONS

Indoor Air Comfort GOLD - Eurofins certified product  
 AgBB - Very low emissions  
 FloorScore - Certified product



#### ENVIRONMENTALLY PREFERABLE FLOORING

Polyflor Colonia PUR achieves a BRE Global Environmental A Rating (Certificate No: ENP 429). Generic EN 15804 Environmental Product Declaration (EPD) available on request. Colonia PUR is 100% recyclable and contains average 40% recycled material. Recyclable via the Recofloor scheme. Visit [www.polyflor.com/environment](http://www.polyflor.com/environment)



Colonia PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention.



#### APPLICATIONS

Colonia PUR is ideal for general domestic use.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email [tech@polyflor.com](mailto:tech@polyflor.com).

At the date of issue the data presented is correct.

\* For clarification regarding slip resistance, consult Polyflor.

VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THESE PRODUCTS INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK  
 UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551  
 EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912  
 RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128  
 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: [INFO@POLYFLOR.COM](mailto:INFO@POLYFLOR.COM)  
 WEBSITE: [WWW.POLYFLOR.COM](http://WWW.POLYFLOR.COM)

James Halstead™  
 FLOORING



2011



Recofloor™  
 Vinyl Take-Back Scheme



COLONIA™  
 FLOORING COLLECTION

WOOD




PERFORMANCE AND  
 PROPERTIES



Refer to BRE Global ratings on [www.greenbooklive.com](http://www.greenbooklive.com)



In collaboration with the European Resilient Flooring Manufacturers' Institute (ERFMI), Polyflor Ltd supports sustainable construction via Environmental Product Declarations (EPDs).



POLYFLOR™  
 COVERING THE WORLD

March 2015

LUXURY VINYL  
 TILES